

US006206041B1

(12) United States Patent Selwyn

(10) Patent No.: US 6,206,041 B1

(45) **Date of Patent:** Mar. 27, 2001

(54) FLUID PRESSURE AMPLIFIER

(76) Inventor: Frederick Philip Selwyn, 3 Efford Park

Business Park, Vicarage Road, Bude

Cornwall EX 23 8LT (GB)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/147,088

(22) PCT Filed: Apr. 2, 1997

(86) PCT No.: PCT/GB97/00936

§ 371 Date: **Jun. 14, 1999** § 102(e) Date: **Jun. 14, 1999**

(87) PCT Pub. No.: WO97/37136

PCT Pub. Date: Oct. 9, 1997

(30) Foreign Application Priority Data

Apr. 2, 1996	(GB)	 9606949
Mar. 3, 1997	(GB)	 9704381

(51) **Int. Cl.**⁷ **F17D 3/00**; F04B 17/00

(52) U.S. Cl. 137/624.14; 417/225

(58) Field of Search 417/225, 53; 137/624.14

(56) References Cited

U.S. PATENT DOCUMENTS

2,945,447 7/1960 Yamaguchi et al. .

FOREIGN PATENT DOCUMENTS

899 903	12/1953	(DE).
0 655 557	5/1995	(EP) .
2 589 900	5/1987	(FR).
6447	5/1913	(GB).
521 783	5/1940	(GB).

^{*} cited by examiner

Primary Examiner—Charles G. Freay
Assistant Examiner—Ehud Gartenberg
(74) Attorney, Agent, or Firm—Miles & Stockbridge P.C.;
John C. Kerins

(57) ABSTRACT

A fluid pressure amplifier is provided, which includes a pipe for flowing fluid and having an array of holes formed therein through which fluid can flow from within the pipe in use, and resiliently-movable obturator means adjacent the pipe and operatively responsive to fluid inlet pressure in the pipe, in which fluid inlet pressure causes the obturator means to oscillate between conditions which alternately permit and prevent fluid from passing through the holes, whereby the fluid leaving the pipe has a pulsed increased pressure. The amplifier is intended for use especially to increase the pressure of water flowing through a pipe submerged in a river, to provide a pumping action to a higher level.

4 Claims, 3 Drawing Sheets

